



STANDARD MANIFOLD INSTALLATION

TYPICAL WATER SERVICE PIPE AND WATER SERVICE VALVE MANIFOLD/TOBY

NOTE:

1. ALL DIMENSIONS IN MILLIMETRES.
2. SERVICE TO BE LAID TO THE CENTRE OF THE FRONT PROPERTY BOUNDARY AND AT RIGHT ANGLES TO STREET BOUNDARY.
3. THE INSTALLATION IS TO UTILISE THE STANDARD MANIFOLD METER SYSTEM WITH THE DOUBLE CHECK AND STRAINER IN THE BODY OF THE MANIFOLD.
4. FOR NEW ALOTMENTS A DUAL/RESTRICTED MANIFOLD SHALL BE INSTALLED. SEE KCDC WS 015.
5. NEW WATER SERVICE INSTALLATIONS OR ALTERED EXISTING WATER SERVICES SHALL BE FITTED WITH DUAL RESTRICTED MANIFOLDS FROM 2009.



STANDARD DETAILS
WATER SERVICE CONNECTIONS
TYPICAL CONNECTIONS WITH MANIFOLD

Drawn	S. TURKINGTON	Designed	J. SAXTON
Approved	M. COLE	Revision Date	OCTOBER 2015
Scale	NOT TO SCALE	Drawing No.	KCDC-WS-011
		Revision	R2