



CONCRETE FOOTING FOR TUBE BASE SOCKETS

1. SAFETY WEDGE SOCKET PEDESTRIAN AREAS

FOR POLE SIZE SEE NOTE 8


CONCRETE DEPTH DEPENDS ON SIGN HEIGHT



2. GRUB SCREW SOCKET NON-PEDESTRIAN AREAS

FOR POLE SIZE SEE NOTE 8

CONCRETE DEPTH DEPENDS ON SIGN HEIGHT



NOTES:

- SIGN TO BE END OR CENTRALLY MOUNTED AS SPECIFIED IN ACCORDANCE WITH NZTA TCD MANUAL SPECIFICATIONS.
- SIGN TO BE MOUNTED EITHER BY SIGNFIX ANTI ROTATION FITTINGS OR EQUIVALENT.
- SIGN TO BE INSTALLED IN ACCORDANCE WITH NZTA TCD SPECIFICATIONS.
- SIGN HEIGHT DEPENDS ON LOCATION, REFER TO RTS 2, MOTSAM AND NZTA TCD SPECIFICATIONS.
- POLE: TO BE 60mm OR 76mm DIAMETER POWDER COATED WHITE ALUMINIUM POST FOR URBAN AREAS.
- WOODEN POSTS: H/4 100mm x 100mm PAINTED WHITE FOR RURAL AREAS.
- TUBE BASE SOCKETS: 400mm FOR POLES UP TO 1.2m HIGH
600mm FOR POLES ABOVE 1.2m HIGH
- POLE TO BE INSERTED INTO TUBE BASE SOCKET AND SECURED WITH A WEDGE OR GRUB SCREW.
- SAFETY SOCKETS, TO BE FLUSH WITH GROUND IN PEDESTRIAN AREAS AND SECURED WITH WEDGE.
- FOUNDATION
- 200x200x400 (FOR 400mm SOCKET)
- 200x200x600 (FOR 600mm SOCKET)



STANDARD DETAILS

ROADING STANDARDS REGULATORY TRAFFIC SIGNS

Drawn	Designed	
T.GE		
Approved	Revision Date	
G.O'CONNOR	APRIL 2018	
Scale	Drawing No.	Revision
NOT TO SCALE	KCDC-RD-014	R5